





Cleaners

SOLVENT STRIPPER

Solvent-based wax stripper for deep removal of greasy oxidation, wax, and existing treatments

SOLVENT STRIPPER is a solvent-based wax stripper to use for the deep cleaning of dirt and organic residues, oxidation, layers of old wax, and existing treatments. Its action works deep down into the textures of the material, helping to dissolve and easily remove even the most stubborn dirt and greasy stains. SOLVENT STRIPPER can be used in combination with ALKALINE CLEANER or WAX REMOVER for a deeper cleaning called "double wax stripping".

BENEFITS

- Ready to use
- Great extractive action
- Gentle on the surface
- Ideal against greasy dirt

USES

Suitable for indoor and outdoor applications.

Suitable for Marble-cement agglomerates, Marble-resin agglomerates, Marblequartz agglomerates, Slate, Sandstone, Basaltina - Lava stone, Molten basalt, Concrete Tiles, Concrete, Craquelé ceramics, Glazed ceramics, Clinker, Cotto, Granite, Polished porcelain tiles, Natural porcelain tiles, Textured porcelain tiles, Limestone, Marble, Reconstituted stone (Eco stone), Porphyry, Quarzite, Terracotta, Travertine, Tuff

COVERAGE

10/15 m²/l

APPLICATION EQUIPMENT

White Pad, Single disk machine

APPLICATION STEPS

Before applying the product it is necessary to take a preliminary test to evaluate the suitability of the product on an unexposed area or unused piece of material Surface Preparation

- Before proceeding with the cleaning, it is advisable to clean away any surface residues, such as dust, debris, and coarse dirt, using a broom or a vacuum cleaner.
- Protect any surface close by that is not meant to be treated.
- Apply the product on surfaces with a temperature between +5 e +40°C
- All surfaces close by not to be treated must be protected

Application

- Pour the undiluted product straight onto the surface being treated.
- Begin to work the product on the surface, rubbing it using the preferred tool.
- Let the product act for 5 10 minutes, continuing to wipe over the surface with your equipment of choice to boost its extractive action.
- Once the time has passed, remove all residues and rinse the whole floor with plenty of water. If the result is only partially achieved, repeat the application process following the same steps.

Resume Surface Use

• After carefully removing any residues and rinsing the surface with water, the floor can be opened to foot traffic



SHOWROOM LINE



APPLICATION STEPS DOUBLE WAX STRIPPING

SOLVENT STRIPPER + ALKALINE CLEANER Before applying the product it is necessary taking a preliminary test to evaluate the suitability of the product on an unexposed area or unused piece of material

Surface Preparation

- Before proceeding with the cleaning, it is advisable to clean away any surface residues, such as dust, debris, and coarse dirt, using a broom or a vacuum cleaner.
- Protect any surface close by that is not meant to be treated.
- Apply the product on surfaces with a temperature between +5 e +40°C
- All surfaces close by not to be treated must be protected

Application

- Pour **SOLVENT STRIPPER** undiluted, straight onto the surface being treated.
- Begin to work the product over the surface, rubbing the surface with the tool of your choice.
- Let the product act for 5 10 minutes, working it every now and then to boost its action.
- Once the indicated time has passed, without removing any residues pour ALKALINE CLEANER or WAX REMOVER directly on the surface following the previously described procedure.
- Once the operations are over remove the residues and then rinse the surface with plenty of clean water.

Resume Surface Use

After carefully removing any residues and rinsing the surface with water, the floor can be opened to foot traffic.

COMPLEMENTARY
MAINTENANCE
PRODUCTS
MANUTENZIONE

After cleaning with **SOLVENT STRIPPER** we recommend using the most suitable Faber cleaner, such as **NEUTRAL CLEANER** or **FLOOR CLEANER**, depending on the nature of the surface.

INSTRUCTIONS AND GUIDELINES

- Do not apply the product on wet or heated surfaces
- When applying to recently laid or grouted surfaces, wait for the adhesive or grout to cure completely.
- Do not use in combination with other chemicals if not specifically required
- Before applying the product it is necessary to take a preliminary test to evaluate its suitability

EQUIPMENT CLEANING

The equipment used can be cleaned with water

PHYSICAL AND TECHNICAL DATA

Formula	Clear Liquid
Color	Amber
Odor	Solvente
Specific gravity at 20°C	$800 \pm 10 \text{ g/l}$
Flammability	30°C open vase



SHOWROOM LINE



STORAGE Keep the container tightly closed and store in a cool, dry place.

SHELF LIFE 36 months in the original, sealed packaging, stored in a cool, dry place.

PACKAGING 1 I bottles - 12 bottles per box

5 I bottles - 4 bottles per box

10 I tanks

ACCIDENTAL Soak up the product with an absorbent material (paper towels, sawdust, **SPILLS**

vermiculite, etc.) and dispose of it in the most suitable waste container.

SAFETY When applying the product, always use suitable personal protective equipment

and follow the instructions on the product safety data sheet with care.

Rev5.0 - 12/09/2022

This technical data sheet supersedes all previous versions. Always refer to the latest version of the data sheet, available on www.fabersurfacecare.com site. Faber Chimica reserves the right to update and/or modify the data and information contained in the datasheet.

The information in this data sheet is based on our wide experience in technical and operational research. In any case, you should always make a preliminary test to verify the suitability of the product for the intended use and the type of material on which it will be applied. The information and the suggestions can't be construed as a commitment or result in our responsibility as the conditions and method of use of the product cannot be controlled by us. Therefore Faber Chimica Srl disclaims any liability concerning the use of such data and suggestions.