Honing and Polishing

CRISTALFAB JT

High performing marble crystallizer to be applied with a red pad.



CIRSTALFAB JT is a mildly acidic liquid product, ready to use, suitable for the crystallization of marble, travertine, and limestone. crystallizing enables you to restore the shine of surfaces that have lost their original sheen due to the use of the surface.

CIRSTALFAB JT restores the shine of the surface on which it is applied with no yellowing nor orange peel.

CIRSTALFAB JT is quick and easy to apply with the Spray Buffing technique, it increases the scratch and chemical aggressions resistance of the material. It doesn't give layering defects and it doesn't alter the slipperiness of the floor as many other crystallizing products on the market do.

CIRSTALFAB JT can also be used to crystallize again areas with high foot traffic that have already been treated in the past.

CHARACTERISTICS AND BENEFITS

- Quick and easy to use
- Ready to use
 - It encreases the surface scratch resistance
- It provides a clear sheen
- No orange peel effect
- No yellowing of the surface
 - No layering defects
 - Long lasting shine

USES

 \checkmark

 \checkmark

 \checkmark

Product **suitable** for marble, limestone; travertine; marble-cement and marble-resin aggomerates.

COVERAGE

For the maintenance of the surface the product covers 50-100 m²/l

APPLICATION EQUIPMENT

Single disk machine of at least 1.5 HP

If looking for a single disk machine, Faber Chimica sells the WARRIOR single disk machine of 2.2 HP, optimized for the professional application of all products.









Honing and Polishing CRISTALFAB JT

High performing marble crystallizer to be applied with a red pad.



APPLICATION STEPS

Prepare the surface

1. Proceed to thoroughly clean the surface making sure to completely remove any dust and residues on the surface. In order to avoid humidifying the surface, we recommend using a broom or a vacuum cleaner.

2. Do not apply CRISTALFAB JT on humid or wet surfaces. Therefore, make sure that the surface is dry.

- 3. We recommend applying the product in sections of 1m² at a time.
- 4. Do not apply CRISTALFAB JT on hot or overheated surfaces.
- 5. Protect the areas not to be treated.

6. We recommend making sure to have on hand a sprayer bottle and to pour CRISTALFAB JT into it before starting the application.

Application

7. Shake it well and then spray a small amount of product directly onto the section of the surface you want to crystallize. Generally, to crystallize a surface of 1 m2 it only takes 2-3 sprays of product.

8. Immediately after spraying the product proceede working it with a single disk machine and a 3M red pad (150 < rpm < 200). Work the product in circular motions evenly thoughout the area.
9. Keep brushing the section until the product is completely dry.

10. Move to the next section and proceede crystallizing the surface as previously described.

11. Once the whole surface has been crystallized, remove any residues or dust if present using a dry cloth or a vacuum cleaner

In cases where the surface is particulary worn out each sections might need from 2-3 applications on each section of the surface

Its formula doesn't give layering defects therefore once the material has been polished the result will be even on the whole area.

COMPLEMENTARY CLEANING AND MAINTENANCE PRODUCTS

- For the everyday cleaning of a surface treated with CRISTALFAB JT, we recommend NEUGEL or ALGAFLOOR



O 900 QUALITY System

Caber SO 1400 ENVIRONMENTAL POLICY

Honing and Polishing CRISTALFAB JT

High performing marble crystallizer to be applied with a red pad.



INSTRUCTIONS AND GUIDELINES

- Never apply the product on wet or damp surfaces.
- Do not apply the product to overly heated surfaces.
- Apply the product to surfaces with a temperature between +5 and +40°C
- When applying to recently laid or grouted surfaces, wait for the adhesive or grout to cure completely.
- Before applying the product to the whole surface, it is advisable taking a preliminary test
- on an unexposed area to check its suitability.

EQUIPMENT CLEANING

At the end of the application, the equipment used can be washed using water.

SAFETY

When applying the product, always use suitable personal protective equipment and follow the instructions on the product safety data sheet with care.

PHYSICAL AND TECHNICAL INFORMATION	
Aspect:	Liquid
Color:	Pink
Odour:	Typical
pH:	3.0± 0.5
Specific gravity (20°C)	1075± 10 g/l

STORAGE

Keep the container tightly closed and store in a cool, dry place.

SHELF LIFE

24 months in the original, sealed packaging, stored in a cool, dry place.

PACKAGING

- 5 I – 4 cans per box



(Taber) SO 9001 QUALITY SYSTEM

Caber SO 1400 ENVIRONMENTAL POLICY

Honing and Polishing CRISTALFAB JT

High performing marble crystallizer to be applied with a red pad.



HAZARD IDENTIFICATION



H302	Harmful if swallowed.
H315	Causes skin irritation.
H318	Causes serious eye damage.
P264	Wash hands thoroughly after handling.
P280	Wear protective gloves/protective clothing/eye protection/face
	protection.
P301+P312	IF SWALLOWED: Call a POISON CENTER/ doctor if you feel unwell.
P305+351+338	IF IN EYES: Rinse cautiously with water for several minutes. Remove
	contact lenses, if present and easy to do. Continue rinsing.
P310	Immediately call a POISON CENTER/doctor

Version 0.0 - 10/07/2020

This technical data sheet supersedes all previous versions. Always refer to the latest version of the data sheet, available on www.fabersurfacecare.com site. Faber Chimica reserves the right to update and / or modify the data and information contained in the data sheet.

The information in this data sheet is based on our wide experience in technical and operational research. In any case you should always make a preliminary test to verify the suitability of the product for the intended use and the type of material on which it will be applied. The information and the suggestions can't be construed as a commitment or result in our responsibility as the conditions and method of use of the product cannot be controlled by us. Therefore Faber Chimica Srl disclaims any liability with regard to the use of such data and suggestions.

 FABER CHIMICA SRL – VIA G.CERESANI, 10 – LOC.CAMPO D'OLMO – 60044 – FABRIANO (AN) – ITALY

 Phone: +39 0732 627178
 Fax: +39 0732 22935

 Email: info@fabersurfacecare.com



Cabers SO 9001 QUALITY SYSTEM

(Taber)